

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Applicants : John S. Kula et al.
Serial No. :
Filed :
Title : STENT WITH VARIABLE WALL THICKNESS

Art Unit :
Examiner :

Honorable Commissioner of Patents
Washington, D.C. 20231

PRELIMINARY AMENDMENT

Dear Sir:

Prior to examination, please amend the above-identified application as follows:

In the Specification:

Page 1, between the title and line 3, before "Field of the Invention" please insert the following:

-- Cross Reference to Related Applications

This application is a continuation of application Serial No. 09/288,406, filed April 8, 1999. --

In the Claims:

Please add the following new claims:

4. A method for making a stent having a geometric shape comprising:
 - providing a metal sheet;
 - rolling said sheet within a pressurized roller to create a textured surface; and
 - cutting a geometric shape into said textured surface.

5. The method of claim 4 wherein same stent comprises:

a generally cylindrical device having a plurality of struts arranged in a circumferential fashion around said cylinder, said cylinder having a generally longitudinal axis, a radial dimension extending from said longitudinal axis, and a circumferential dimension extending around said axis, and said struts interconnected with one another;

said struts having a length, and said stent capable of being expanded from a first diameter to a second expanded diameter;

said struts having a cross-section comprising a width in said circumferential dimension and a thickness in said radial dimension;

and said strut thicknesses variable along their lengths.

6. The stent of claim 4 used in combination with a balloon catheter.

7. The stent of claim 4 wherein said stent is self-expanding.

8. A stent as in claim 4 wherein said variable strut thickness is varied along the length of the strut so that said strut is thicker at its ends than in its middle.

9. The stent of claim 4 wherein said struts are configured so that there are portions of relative thickness and relative thinness along the length of the stent, and said portions of relative thickness are interspersed between said portions of relative thinness.

10. The stent of claim 4 wherein the stent has a portion of relative thickness at one of said ends, and a portion of relative thinness at a second of said ends.

Serial No. 09/_____


REMARKS/ARGUMENTS

Claims 4-10 remain in this application.

Attached hereto is a marked-up version of the changes made to the specification and claims by the current amendment. The attached page(s) is/are captioned "Version with markings to show changes made".

Applicant respectfully requests that a timely Notice of Allowance be issued in this case.

Respectfully submitted,



By:

Paul A. Coletti
Reg. No. 32,019

Johnson & Johnson
One Johnson & Johnson Plaza
New Brunswick, NJ 08933-7003
(732) 524-2815
Dated: October 12, 2001

VERSION WITH MARKINGS TO SHOW CHANGES MADE

In the Specification:

Page 1, between the title and line 3, before "Field of the Invention" please insert the following:

-- Cross Reference to Related Applications

This application is a continuation of application Serial No. 09/288,406, filed April 8, 1999. --

In the Claims:

Please add the following new claims:

4. A method for making a stent having a geometric shape comprising:

providing a metal sheet;
rolling said sheet within a pressurized roller to create a textured surface; and
cutting a geometric shape into said textured surface.

5. The method of claim 4 wherein same stent comprises:

a generally cylindrical device having a plurality of struts arranged in a circumferential fashion around said cylinder, said cylinder having a generally longitudinal axis, a radial dimension extending from said longitudinal axis, and a circumferential dimension extending around said axis, and said struts interconnected with one another;

said struts having a length, and said stent capable of being expanded from a first diameter to a second expanded diameter;

said struts having a cross-section comprising a width in said circumferential dimension and a thickness in said radial dimension;

and said strut thicknesses variable along their lengths.

6. The stent of claim 4 used in combination with a balloon catheter.

Serial No. 09/_____

7. The stent of claim 4 wherein said stent is self-expanding.
8. A stent as in claim 4 wherein said variable strut thickness is varied along the length of the strut so that said strut is thicker at its ends than in its middle.
9. The stent of claim 4 wherein said struts are configured so that there are portions of relative thickness and relative thinness along the length of the stent, and said portions of relative thickness are interspersed between said portions of relative thinness.
10. The stent of claim 4 wherein the stent has a portion of relative thickness at one of said ends, and a portion of relative thinness at a second of said ends.